ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

BOPP Adhesive Tape Jumbo Rolls - Quality Certificate

BOPP 薄膜 — 检测数据摘录

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-COC-TAPE-2026	**Rev. 2.0**	**2026-11-09**	**Test Data Extract / 检测数据摘录**

1 • DOCUMENT INFORMATION 文档信息

Item 项目	Description 说明
Document type 文件类型	Test Data Extract / 检测数据摘录
Subject 主题	BOPP Adhesive Tape Jumbo Rolls - Quality Certificate
Content basis 内容来源	Original technical document (archived) 原始技术资料（已归档）
Re-issue 重排发行	2026-11-09 · Rev. 2.0
Language 语言	Bilingual headings — English / 中文；正文依据原件转录

2 • TECHNICAL CONTENT 技术内容

QUALITY CERTIFICATE BOPP self-adhesive packaging tape is composed of biaxial-oriented polypropylene (BOPP) film and adhesive covering based on Acrylic polymer. This BOPP tape supplied in jumbo rolls is used for production of narrower BOPP tape rolls for sealing of cartons and other purposes. The BOPP tape is available clear, brown, yellowish and colored.

以下内容提取自原始技术资料，并按本公司统一版式重排；数值与结论依据原件转录。

36, 38, 40, 43, 45, 47, 49, 50, 59 BOPP PACKING TAPE JUMBO ROLL’ S Roll’ s width, mm 1280±20 1280±20 1280±20 1280±20 1280±20 Roll’ s length, m 4000±200 4000±200 4000±200 4000±200 4000±200 Total Thickness of tape, mic 36 38 40 43 45 BOPP Film Thickness, mic 23 23 23 23 25 Acrylic polymer covering thickness, mic 13 15 17 20 20 Color of tape WHITE CLEAR Type of adhesive Water base Water base Water base Water base Water base Tensile strength 12kg/mm2, 70N/2.5CM. 13kg/mm2, 70N/2.5CM.

14kg/mm2, 70N/2.5CM. 14.5kg/mm2, 80N/2.5CM. 15kg/mm2 75N/2.5CM., 180° peel adhesion 450g/in, ≥ 4.6N/2.5 CM 450g/in, ≥ 5.0N/2.5 CM 450g/in, ≥ 5.4N/2.5 CM 450g/in, ≥ 6.

0N/2.5 CM 450g/in, ≥ 6.4N/2.5 CM Temperature resistance 115 115 115 115 115 Temperature mode of application -60&+80 -60&+80 -60&+80 -60&+80 -60&+80 Elongation at break 100% 105% 110% 115% 120% Test temperature -10 -10 -10 -10 -10 Test humidity ≥120% ≥130% ≥150% ≥170% ≥180% Initial tack (14#) ≥10 ≥12 ≥14 ≥16.5 ≥18.5 Holding power >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM Eastern Communication ·

QUALITY CERTIFICATE BOPP self-adhesive packaging tape is composed of biaxial-oriented polypropylene (BOPP) film and adhesive covering based on Acrylic polymer. This BOPP tape supplied in jumbo rolls is used for production of narrower BOPP tape rolls for sealing of cartons and other purposes. The BOPP tape is available clear, brown, yellowish and colored.

36, 38, 40, 43, 45, 47, 49, 50, 59 BOPP PACKING TAPE JUMBO ROLL’ S Roll’ s width, mm 1280±20 1280±20 1280±20 1280±20 Roll’ s length, m 4000±200 4000±200 4000±200 3300±150 Total Thickness of tape, mic 47 49 50 60(59) BOPP Film Thickness, mic 25 28 28 37 Acrylic polymer covering thickness, mic 22 21 22 22 Color of tape WHITE CLEAR yellowish Type of adhesive Water base Water base Water base Water base Tensile strength 15.5kg/mm2,70N/2.5CM. 16kg/mm2,70N/2.5CM. 16kg/mm2, 80N/2.5CM.

180° peel adhesion 450g/in, ≥ 6.8N/2.5 CM 450g/in, ≥ 7.2N/2.5 CM 450g/in, ≥ 7.2N/2.5 CM 450g/in, ≥ 9.2N/2.5 CM Temperature resistance 115 115 115 115 Temperature mode of application -60&+80 -60&+80 -60&+80 -60&+80 Elongation at break 125% 130% 130% 160% Test temperature -10 -10 -10 -10 Test humidity ≥190% ≥200% ≥200% ≥250% Initial tack (14#) ≥20 ≥20 ≥22 ≥22 Holding power >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM Eastern Communication ·

ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

3 • NOTES 说明

Re-typeset content extract from the original technical document. Third-party issuing bodies, report numbers, signatures, seals, factory addresses, personal contacts and watermarks have been removed. Values are transcribed from the source and are indicative; the signed technical agreement governs any order.
本文件依据原始技术资料提取内容后重新排版，已移除第三方出证机构、报告编号、签名盖章、工厂地址、个人联系方式与水印。数值按原件转录，仅供参考，订单执行以正式技术协议为准。