ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

Technical Data Sheet — BOPP Two-Side Heat Sealable Film (15–48 μm)

BOPP 薄膜 — 技术数据

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-TDS-BOPP-2SHS-2026	**Rev. 2.0**	**2026-11-09**	**Technical Data / 技术数据**

1 • DOCUMENT INFORMATION 文档信息

Item 项目	Description 说明
Document type 文件类型	Technical Data / 技术数据
Subject 主题	Technical Data Sheet — BOPP Two-Side Heat Sealable Film (15–48 μm)
Content basis 内容来源	Original technical document (archived) 原始技术资料（已归档）
Re-issue 重排发行	2026-11-09 · Rev. 2.0
Language 语言	Bilingual headings — English / 中文；正文依据原件转录

2 • TECHNICAL CONTENT 技术内容

抗静电与滑爽性能良好	转换加工与复合
• Both sides heat sealable , one side treated	•Confectionerypacking
双面热封 单面处理 、	糖果包装
• Good optics: high gloss , low haze	•Biscuitoverwrap
光学性能好：高光泽 低雾度 、	饼干外包装
•Highsealintegrity	•Packagingofindustrialandfoodproductsincasings
热封强度高	工业与食品的套筒式包装
•MeetsFDAregulationsfordirectfoodcontact	• Vertical or horizontal automatic packing with end -flap or
符合FDA直接接触食品规定	overlapseals
	立式或卧式自动包装机的端封与搭接封

Tables below are transcribed from the source; blank or illegible cells are shown as —.
以下表格依据原件转录；空白或不可辨单元格以 — 表示。

O O C | S us a st ct, e e , u , C a 86 55 6 68 85 sa es@bopp sa es.co APIG-TDS-BOPP-2SHS-2018 | Issued 2018-09-25 | 亚太工业集团有限公司 Page 1 BOPP Two-Side Heat Sealable Film BOPP 双面热封膜 TECHNICAL DATA SHEET 技术数据表 | APIG-TDS-BOPP-2SHS-2018 | Issued 2018-09-25 PRODUCT DESCRIPTION 产品描述 A transparent biaxially oriented polypropylene film, heat sealable on both sides and corona treated on one side.

以下内容提取自原始技术资料，并按本公司统一版式重排；数值与结论依据原件转录。

The film contains an anti-block and antistatic additive package that provides excellent machinability in automatic packaging lines. The untreated side offers a wide sealing range; the treated surface is on the outside of the roll and is intended for printing and lamination.

双向拉伸聚丙烯透明薄膜，双面可热封，单面电晕处理。膜内含有防粘与抗静电添加剂，在各类自动包装机上运行顺畅。未处 理面热封窗口宽，处理面位于卷材外侧，用于印刷与复合。 KEY FEATURES 主要特点 APPLICATIONS 应用 • Good antistatic and slip properties 抗静电与滑爽性能良好 • Conversion and lamination 转换加工与复合 • Both sides heat sealable, one side treated 双面热封、单面处理 • Confectionery packing 糖果包装 • Good optics:

high gloss, low haze 光学性能好：高光泽、低雾度 • Biscuit overwrap 饼干外包装 • High seal integrity 热封强度高 • Packaging of industrial and food products in casings 工业与食品的套筒式包装 • Meets FDA regulations for direct food contact 符合 FDA 直接接触食品规定 • Vertical or horizontal automatic packing with end-flap or overlap seals 立式或卧式自动包装机的端封与搭接封 STANDARD DIMENSIONS 标准规格与卷重 Thickness 厚度 (μm) Weight 克重 (g/m²) Width 卷宽 (mm) I.D.

纸芯 (mm) Length 长度 (m) 550 mm OD Weight 卷重 (kg) 550 mm OD Length 长度 (m) 760 mm OD Weight 卷重 (kg) 760 mm OD 15 13.6 400–2000 3"–6" 13 900 1.89 27 800 3.77 17.5 15.8 400–2000 3"–6" 11 900 1.89 23 800 3.77 20 18.1 400–2000 3"–6" 10 300 1.89 20 600 3.77 25 22.6 400–2000 3"–6" 8 250 1.89 16 500 3.77 30 27.2

ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

400–2000 3"–6" 6 900 1.89 13 800 3.77 35 31.7 400–2000 3"–6" 5 900 1.89 11 800 3.77 40 36.2 400–2000 3"–6" 5 150 1.89 10 300 3.77 50 45.3 400–2000 3"–6" 4 150 1.89 8 300 3.77 Width range 400–2000 mm;

core I.D. 3"–6"; other thicknesses on request. 卷宽 400–2000 mm，纸芯 3"–6"，其余厚度可订制。 Typical values on the following page. 典型值见下页。 · O O C | S us a st ct, e e , u , C a 86 55 6 68 85 sa es@bopp sa es.co APIG-TDS-BOPP-2SHS-2018 | Issued 2018-09-25 | 亚太工业集团有限公司 Page 2 TYPICAL VALUES 典型值 Values are typical and not a specification limit; test methods per ASTM. 数值为典型值，非规格上下限；测试方法按 ASTM。 PROPERTY 性能 TEST AST M UNIT 单位 15 18 20 22 25 30 35 40 48 50

THICKNESS 厚度 Inter nal Micro n 15 18 20 22 25 30 35 40 48 50 （Gauge 线规） 60 72 80 88 100 120 140 160 192 200

FILM DENSITY 薄膜密度 D-15 05 g/cm³ 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 GRAMMAGE 克重 Inter nal g/m² 13.50 16.20 18.00 19.80 22.50 27.00 31.50 36.00 43.20 45.00 YIELD 出率 Inter nal m²/kg 74.07 61.73 55.56 50.51 44.44 37.04 31.75 27.78 23.15 22.22 in²/lb 5218 5 4349 1 3914 4 3558 6 3130 9 2609 6 2236 9 1957 2 1631 0 1565 4

TREATMENT LEVEL 表面张力 D-25 78 dyne/ cm 38 38 38 38 38 38 38 38 38 38 COEFF. OF FRICTION (dynamic) 动摩擦系数 D-18 94 — 0.35 0.35 0.35 0.35 0.30 0.30 0.30 0.30 0.30 0.30 HAZE 雾度 D-10 03 % 2.0 2.2 2.3 2.3 2.5 2.5 2.6 2.8 2.9 2.9 GLOSS 光泽度 D-24 57 Unit 85 85 85 85 85 80 80 80 80 80

3 • NOTES 说明

Re-typeset content extract from the original technical document. Third-party issuing bodies, report numbers, signatures, seals, factory addresses, personal contacts and watermarks have been removed. Values are transcribed from the source and are indicative; the signed technical agreement governs any order.
本文件依据原始技术资料提取内容后重新排版，已移除第三方出证机构、报告编号、签名盖章、工厂地址、个人联系方式与水印。数值按原件转录，仅供参考，订单执行以正式技术协议为准。