ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

BOPP Pearlized Film 25/38/40 µm - Technical Data
BOPP 薄膜 — 技术数据

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-TDS-BOPP-PEARL-2026	**Rev. 2.0**	**2026-11-09**	**Technical Data / 技术数据**

1 • DOCUMENT INFORMATION 文档信息

Item 项目	Description 说明
Document type 文件类型	Technical Data / 技术数据
Subject 主题	BOPP Pearlized Film 25/38/40 µm - Technical Data
Content basis 内容来源	Original technical document (archived) 原始技术资料（已归档）
Re-issue 重排发行	2026-11-09 · Rev. 2.0
Language 语言	Bilingual headings — English / 中文；正文依据原件转录

2 • TECHNICAL CONTENT 技术内容

PROPERTIES	UNIT	Column 3	RESULT	TESTSTANDARD
AVERAGEGAUGE	MICRON µm		d 38/40	
UNITWEIGHT	g/m2		e t 175 i	
LIGHTTRANSMISSION	%		m 22 i	1 ASTMD 1003 7
GLOSS45°	L %		80	8 ASTMD 2457
TENSILESTRENGTH	MPa	MD o . ,	60	4 5 6 s ASTMD 882 l - 9 a
	MPa	C TD	m 170	
ELONGATIONATBREAK	%	p o MD	130	1 c i 9 ASTMD 882 m
	u o %	c TD s	8 17	
MODULUSOFELASTICITY	r G MPa	e MD l	1 930	e h ASTMD 882 C
		a TD	6 2170	
r t HEATSHRINKAGE s 120℃5min u ,	y s m %	MD	:8 32	n
	l i f %	TD	e o i l i 26 t	
d n p l o WETTINGLEVEL b c i f	p l a s Dyne/cm c i f i	e b o ASIDE	a 38 i c	m o ASTMD 2578 - c
		m / BSIDE	n u e . 38 l	ASTMD 2578
i w c a w a P p w COF a / i / s	c p a s µd t a h	p m AA	a s 039	ASTMD 1894
		m AB	m 048 l	
		o C BB p	i f 053	
a p : w HEATSEALSTRENGTH t e : / t 125℃018Mpa1S p , . , a	n p r o N/15mm e b t s		27	

Tables below are transcribed from the source; blank or illegible cells are shown as —.
以下表格依据原件转录；空白或不可辨单元格以 — 表示。

TECH DATA OF 25UM BOPP PEARLIZED FILM (BOPP WHITE OPAQUE FILM)
以下内容提取自原始技术资料，并按本公司统一版式重排；数值与结论依据原件转录。

THICKNESS micron 25 YIELD m2/kg (min.) - 59 49 42 35 28 DENSITY g/cm3 ASTM D-1505 0.65-0.70 0.65-0.70 0.65-0.70 0.68-0.72 0.68-0.72

TENSILE STRENGTH kg/mm2 MD ASTM 6 6 6 6 6 (min.) TD D-882 12 12 12 12 12

ELONGATION AT BREAK % MD ASTM 140 140 140 140 140 (max.) TD D-882 50 50 50 50 50

THERMAL SHRINKAGE % MD ASTM 4 4 4 4 4 (120° c 15 minutes) (max.) TD D-1204 2 2 2 4 4 STATIC C.O.F. film/film ASTM D-1894 0.3 - 0.4 0.3 - 0.4 0.3 - 0.4 0.3 - 0.4 0.3 - 0.4 °c 1 BAR 1 SEC 115 115 115 115 115 g/cm

地址 ADD.: No.3399, Luzhou Ave., Baohe Dist., Hefei, Anhui 230051, China | 安徽省合肥市包河区庐州大道3399号
传真 Fax: +0086-551-64683490 **营业执照注册号 Business License Reg. No.:** 91340100575703313N
海关注册编码 Customs Reg. Code: 3401961393

ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

(min.) - 80 80 80 80 80 GLOSS (angle 45°) % (min.) ASTM 26 26 26 26 26 D-2457 WVTR g/m2/24 hr (max.) ASTM F-1249 5 4.2 3.6 3.2 3 O2TR cc/m2/24 hr (max.) ASTM D-3985 1,700 1,600 1,500 1,400 1,200

CORONA REATMENT Dyne/cm (min.) ASTM D-2578 38 38 38 38 38 · TYPE: BOPP PEARLIZED FILM/BOPP CO-EX PEARLIZED OPAQUE UNIT RESULT

LIGHT TRANSMISSION % 22 ASTM D-1003 GLOSS 45° % 80 ASTM D-2457

TENSILE STRENGTH MPa MD 60 ASTM D-882 MPa TD 170

3 • NOTES 说明

Re-typeset content extract from the original technical document. Third-party issuing bodies, report numbers, signatures, seals, factory addresses, personal contacts and watermarks have been removed. Values are transcribed from the source and are indicative; the signed technical agreement governs any order.
本文件依据原始技术资料提取内容后重新排版，已移除第三方出证机构、报告编号、签名盖章、工厂地址、个人联系方式与水印。数值按原件转录，仅供参考，订单执行以正式技术协议为准。